

## DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

No. ME110-20131028

**1. Unique identification code of the product-type:**

*ME 110*

**2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

*batch number: see packaging of the product*

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

*Self-adhesive bitumen damp proof sheets including bitumen basement tanking sheets  
According DIN EN 13969: 2007*

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

*Tremco illbruck Produktion GmbH  
Werner-Haepf-Straße 1  
D-92439 Bodenwöhr*

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

*Not relevant*

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

*System 2+  
System 3 for reaction to fire*

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

*Notified Body SKZ-TeConA GmbH (identification no. 1213) performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC no. 1213-CPD-5111*

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

*Not relevant*

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	class E	DIN EN 13969:2007-03
Tensile properties		
Longitudinal strength	≥ 200N/50mm	
Transverse strength	≥ 200N/50mm	
Longitudinal elongation	≥ 150%	
Transverse elongation	≥ 150%	
Resistance to static loading	Method B: 5kg	
Tear resistance	≥ 140N	
Impact resistance	≥ 200mm (Method A)	
	≥ 600mm (Method B)	
Joint strength	≥ 200N/50mm	
Low temperature flexibility	≤ -30°C	
Watertightness	pass	
Durability against aging	pass	
Durability against chemicals	pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Walter Geyer, managing director  
(name and function)

Bodenwöhr, 28.10.2013 (place and issue)



.....  
(signature)